



SUE16K

LFP Battery 16.07kWh Floor-standing

磷酸铁锂电池 16.07kWh 落地式

- 

Floor-standing design
落地式安装设计
- 

Built-in BMS management
内置BMS智能管理
- 

Grade-A cells, 8000 cycles
A级电芯，循环寿命8000次
- 

CAN/RS485 inverter protocol
支持主流逆变器协议
- 

Parallel expansion supported
支持并联扩容
- 

IP21/IP65 optional
IP21/IP65可选

规格参数Specifications

型号Model	SUE16K
设计样式Case design	落地式 Floor-standing
电池类型Battery Type	磷酸铁锂LiFePO4
电压 Normal Battery Voltage (Vdc)	51.2V
容量 Normal Capacity (25℃ 0.2C)(Ah)	314Ah
能量 Normal Capacity (25℃ 0.2C)(Ah)	16076WH
浮充电压 Float Charge Voltage (Vdc)	56.0V
电压范围 Operation Voltage range (Vdc)	40.0~58.4V
最大连续充电电流 (A) Max Continuous Charge Current (A)	200A
最大连续放电电流 (A) Max Continuous Discharge Current (A)	200A
最大脉冲放电电流 (A) Max Pulse Discharge Current (A)	300A 1Sec
端子 Terminal	M8
存储温度Storage temperature	0℃~30℃
防护等级IP degree	IP 20
存储期限Storage duration	6月months at 25℃
安全标准Safety standard	UN38.3,MSDS
显示Display(可选Optional)	LCD
通讯Communication	CAN,RS485
保护Protection	
保护Protect	过充保护、过放保护、过流保护、短路保护、过温保护 Overcharge Protection, Over Discharge Protection, Over-Current Protection, Short Circuit Protection, Over Temperature Protection
环境Environment	
工作温度 Working Temperature	-10℃~+50℃
湿度Humidity	0~95%(no condensation)
最高海拔Sea Level(m)	≤1500
结构形状 Structural shape	
产品尺寸 Product Dimensions (mm)	800×410×286 mm
包装尺寸 Packaging Dimensions (mm)	980×540x376 mm
净重 Net Weight (kg)	118Kg
毛重 Gross Weight (kg)	132Kg